

Power Supplies

Single-phase input voltage
750 mA



4,620.-



Output current	0.75 A									
Output power	18 W									
Output voltage	24 V DC (SELV)									
Input voltage	100...240 V AC									
Model (โมเดล)	BAE PS-XA-1W-24-007-001									
Input voltage range	90...264 V AC/120...375 V DC									
Inrush current	115 V AC < 10 A/230 V AC < 18 A									
Frequency range	47...63 Hz									
Input fuse	T2 A/250 V AC internal									
Voltage adjustment range	21.6...28.8 V DC									
Temperature coefficient	±0.03 %/°C									
Ripple & noise	50 mV									
Holdup time	115 V AC > 20 ms/230 V AC > 30 ms									
Status indicator DC ON	Green LED									
Status indicator DC LOW	Red LED									
Efficiency	77 %									
Response	Hiccup mode									
Switching frequency	> 100 kHz									
Isolation voltage	3000 V AC									
Isolation resistance	100 MΩ									
Turn-on delay	< 1 s									
Ambient temperature range	−25...+71 °C									
Derating	−3 %/°C above +61 °C									
Parallel mode	Yes (with external diodes)									
Degree of protection as per IEC 60529	IP 20									
Ready output	No									
Cooling	Air convection									
Housing material	Plastic									
Weight	0.15 kg									
Approvals	CE, UL/cUL, TÜV									
Wiring diagram	<table><tr><td>L, N</td><td>Input terminals</td></tr><tr><td>PE</td><td>PE connection</td></tr><tr><td>Vo −</td><td>Output terminal −</td></tr><tr><td>Vo +</td><td>Output terminal +</td></tr></table>	L, N	Input terminals	PE	PE connection	Vo −	Output terminal −	Vo +	Output terminal +	
L, N	Input terminals									
PE	PE connection									
Vo −	Output terminal −									
Vo +	Output terminal +									

*SELV = Safety Extra Low Voltage

